

ANTERONIAMES OF THE CA

TO ARE TO WHOM THESE PRESENTS SHAVE COMES

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office

May 04, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/459,655

FILING DATE: April 02, 2003

P1 1164427

RELATED PCT APPLICATION NUMBER: PCT/US04/07568

By Authority of the COMMISSIONER OF PATENTS AND TRADEMARKS

M. TARVER Certifying Officer

PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN COMPLIANCE WITH RULE 17.1(a) OR (b)

PTO/SB/16 (10-01)

Approved for use through10/31/2002. OMB 0651-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Office information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53(c). Express Mail Label No.

Express Mail Label No. EU748999789US	C				
INVENTOR(S)	<u></u>				
Given Name (first and middle [if any]) Family Name or Surname (City and either State or Foreign Country)					
Donald W. Daniel L. HAYWARD WITHAM Waterville, Ohio Maumee, Ohio					
Additional inventors are being named on the separately numbered sheets attached hereto					
TITLE OF THE INVENTION (500 characters max)					
METHOD FOR TREATING RECYCLED POLYETHYLENE TEREPHTHALATE CONTAINING MELTING CONTAMINANTS					
Direct all correspondence to: CUSTOMER Number OR Type Customer Number here CORRESPONDENCE ADDRESS THE HAME HAME MAN DEF	• ,				
Firm or PATENT TRADEMARK OFFICE Individual Name	_				
Address					
Address City					
Country State ZIP	$\neg \neg$				
Telephone 419-874-1100 53x 419-874-1120					
Specification Number of Pages 8 CD(s); Number Drawing(s) Number of Sheets Application Data Sheet. See 37 CFR 1.76 Application Data Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT					
A check or money order is enclosed to cover the filing fees The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number Payment by credit card. Form PTO-2038 is attached.					
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government. No. Yes, the name of the U.S Government agency and the Government contract number are:					
PIGNATURE Date 04/02/2003 REGISTRATION NO. 17,919					
TPED OF PRINTED NAME Donald R. Fraser (if appropriate)					
ELEPHONE 419-874-1100 Docket Number: 1-36904					

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C.

CERTIFICATE OF MAILING BY "EXPRESS MAIL" (37 CFR 1.10) Applicant(s): Donald W. Hayward et al.			Docket No. 1-36904
Serial No.	Filing Date	Examiner	Group Art Unit
Invention: METHOD FO MELTING C	OR TREATING RECYCLED PO ONTAMINANTS	LYETHYLENE TEREPHTHALAT	TE CONTAINING
I hereby certify that the	following correspondence:)	
Provisional Patent A	pplication		
	(Identify type o	f correspondence)	
	elope addressed to: The Assistar	e "Express Mail Post Office to Ado	•
		Dolores Slowinski (Typed or Printed Name of Person Mailing Solores Slowen	Correspondence)
	Participants and	(Signature of Person Mailing Corre	•
		("Express Mail" Mailing Label I	Number)

Note: Each paper must have its own certificate of mailing.

TITLE

METHOD FOR TREATING RECYCLED POLYETHYLENE TEREPHTHALATE CONTAINING MELTING CONTAMINANTS

5 FIELD OF THE INVENTION

This invention relates generally to a process for treating recycled polyethylene terephthalate (RPET) containing contaminants. More particularly, the invention is directed to a process for treating contaminated RPET, so that the small amounts of melting contaminants contained in the RPET flakes have a negligible effect on the article ultimately produced from the RPET melt.

15 BACKGROUND OF THE INVENTION

Post-consumer processing of recycled PET to manufacture a variety of low-tech consumer products such as flower pots and fence posts is well-known. Typically, the recycling process utilizes used PET containers, such as discarded carbonated beverage 20 containers, which are collected, sorted, washed, and separated from contaminants to yield a relatively clean source of RPET. Additionally, the manufacture of imperfect and damaged molded PET products, particularly the blow molded bottles used for containing consumer 25 goods, results in a considerable amount of PET waste which the manufacturers of such products would like to The RPET produced by conventional recycling processes is generally in ground or flake form, which is thereafter melt processed or further pelletized by the 30

end user.

30

RPET is generally subjected to a grinding operation in order to make the material easier to handle and process. Conventional grinding equipment reduces the RPET to about 3/8 inch particles or flakes. grinding is conducted in a manner to insure that a consistent flake size will be produced, by employing a grate or screen through which the ground material must pass upon exiting the grinder. Although conventional RPET flakes melt processing and pelletizing equipment is 10 designed to handle 3/8 inch flakes, some RPET materials having sizes as large as $\frac{1}{2}$ inch and as small as $\frac{1}{2}$ inch are also commercially produced. The bulk density of 3/8 inch flake RPET generally ranges from about 22 to about 35 pounds per cubic foot. 15

Due to the nature of the recycling process, numerous polymeric contaminants are typically found in RPET flakes. These contaminants may be classified generally as either melting or non-melting contaminants.

- Melting contaminants are those which melt at or below the melting temperature of polyethylene terephthalate (PET), while non-melting contaminants are those which melt at temperatures above the melt temperature of PET. Examples of melting contaminants include PVC, Nylon,
- Polyethylene, Polypropylene, EVOH, Polystyrene, and the like.

It is known that melting contaminants degrade rapidly in the RPET melt stream of, for example, a melt extruder. Melting contaminants often cause yellowing and a loss of intrinsic viscosity in the RPET plastic

stream. Likewise, such contaminants often form discrete areas of very dark inclusions or gels within the RPET plastic matrix.

It would be desirable to treat contaminated RPET,

5 so that small amounts of melting contaminants would have
only a negligible effect on RPET melting operations.

SUMMARY OF THE INVENTION

Accordant with the present invention, a process for treating RPET flakes which contain melting contaminants, so that the melting contaminants have only a negligible effect during the RPET melting and forming operations, has surprisingly been discovered. The process comprises providing a quantity of RPET flakes having melting contaminants, comminuting the RPET flakes to prepare RPET particles having an average mean particle size less than about 300 microns, melting the RPET particles to prepare an RPET melt, and mixing the RPET melt.

The inventive process is particularly useful for preparing a polymer melt from RPET flakes, which melt is ultimately used for the processing and forming of, for example, plastic containers.

20

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The present invention is directed to a process for treating RPET flakes, comprising providing a quantity of RPET flakes having melting contaminants, comminuting the RPET flakes to prepare RPET particles having an average mean particle size less than about 300 microns, melting

the RPET particles to prepare an RPET melt, and mixing the RPET melt.

By the term "RPET flakes" as it is used herein is meant generally the commercially available recycled polyethylene terephthalate materials produced by conventional PET recycling methods, usually in flake form, but which may additionally be in the form of chunks, spheres, pellets, and the like, and which are generally made available in bulk in a substantially uniform particle size from about % inch to about % inch.

According to the present invention, a quantity of RPET flakes containing melting contaminants is provided for further processing. The quantity of RPET flakes provided in the initial step of the inventive process may easily be determined by a routineer in the art of polymer processing, depending upon the quantity of polymer melt desired for further processing.

10

20

According to the present invention, the RPET flakes are comminuted by any conventional means to prepare RPET particles having an average mean particle size less than about 300 microns.

Following comminution of the RPET flakes, the resultant RPET particles are melted by conventional means such as, for example, by adding the neet or pelletized RPET particles to a melt extruder, or to a high shear device.

Finally, the RPET melt is thoroughly mixed together by conventional means. Conveniently, if a melt extruder or high shear device is used in the previous step, the mixing will occur simultaneously with either of those

operations.

This polymer blend component is beneficial for combining with other polymer materials for subsequent melt processing and forming operations. For example, the addition of the inventive RPET melt to a quantity of virgin polyethylene terephthalate will extend the volume of the virgin PET.

If an RPET melt were prepared directly from the original RPET flakes, the resultant melt would be considered unusable or of low quality. The inventive process, however, converts this erstwhile useless RPET material into a higher grade of RPET which may be useful even for the manufacture of food grade containers.

The process for treating RPET flakes containing

melting contaminants described hereinabove is generally disclosed in terms of its broadest application to the practice of the present invention. Occasionally, the process conditions as described may not be precisely applicable to each RPET/contaminant combination included within the disclosed scope. Those instances where this occurs, however, will be readily recognized by those ordinarily skilled in the art. In all such cases, the process may be successfully performed by conventional modifications to the disclosed method.

The invention is more easily comprehended by reference to specific embodiments recited hereinabove which are representative of the invention. It must be understood, however, that the specific embodiments are provided only for the purpose of illustration, and that the invention may be practiced otherwise than as

specifically illustrated without departing from its spirit and scope.

WHAT IS CLAIMED IS:

10

1. A process for treating RPET flakes, comprising: providing a quantity of RPET flakes having melting contaminants;

comminuting the RPET flakes to prepare RPET particles having an average mean particle size less than about 300 microns;

melting the RPET particles, to prepare an RPET melt; and

mixing the RPET melt.

ABSTRACT

A process for treating RPET flakes comprises providing a quantity of RPET flakes having melting contaminants, comminuting the RPET flakes to prepare RPET particles having an average mean particle size less than about 300 microns, melting the RPET particles to prepare an RPET melt, and mixing the RPET melt.

10

15

20

25

30